



# DET NORSKE VERITAS

## EC TYPE-EXAMINATION CERTIFICATE

Application of: Council Directive 96/98/EC of 20 December 1996 on Marine Equipment as amended by directive 2009/26/EC, issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Directorate. This Certificate is issued by Det Norske Veritas under the authority of the Government of the Kingdom of Norway.

CERTIFICATE NO. **MED-B-5966**

This is to certify that the  
**"B" Class divisions, fire integrity**


with type designation(s)  
**EB025**

Manufacturer  
**Contech as**  
**ARENDAL, Norway**

is found to comply with the requirements in the following Regulations/Standards:  
Annex A.1, item No. A.1/3.11b and Annex B, Module B in the Directive. SOLAS 74 as amended, Regulation II-2.3.4.4. and IMO FTP Code.

Further details of the equipment and conditions for certification are given overleaf.

Høvik, 2010-04-20  
for Det Norske Veritas AS



This Certificate is valid until  
**2015-04-20**

**Eivind Mykland**  
Head of Department

Notified Body No.: **0575**

DNV local office:  
**Kristiansand S**

**Amir Dzaferi**  
Surveyor



The Certificate is subject to terms and conditions overleaf. Any significant changes in design or construction of the product, or amendments to the Directive or Standards referenced above may render this Certificate invalid. The product liability rests with the manufacturer or his representative in accordance with Council Directive 96/98/EC, as amended. The Mark of Conformity may only be affixed to the product and a Declaration of Conformity may only be issued when the production/product assessment module referred to in the council directive, is fully complied with.



Certificate No.: MED-B-5966  
Item No.: A1/3.11b  
Job Id.: 344.1-002412-1

## Product description

"EB025"

bulkhead consist of panels made of 0.56 mm galv. steel plates with PVC coating on unexposed side and insulated with a core of 25 to 125 mm Paroc fire Slab 150/337-00 with density 140 kg/m<sup>3</sup>.

The thickness of panels may be in range from 25 mm to 125 mm.

The panels are fitted together with joints of type B.

For further details see the test reports mentioned under Type Examination documentation below.

## Application/Limitation

Approved for use in a fire retarding division of class B-15.

Max. panel width 600 mm.

The insulation material, adhesive and surface materials used have to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

Each product is to be supplied with its manual for installation and use.

## Type Examination documentation

Test report No. 22N002.16 dated 10 December 1998 and assessment No. 22N000.10/99.072a dated 5 March 1999 from SINTEF, Norway.

Tested according to IMO FTPC Part 3 (IMO Res. A.754(18)).

## Marking of product

The product is to be marked with name of manufacturer, type designation, fire technical rating, MED Mark of Conformity and USCG approval number if applicable (see below).

## Mark of Conformity

The manufacturer is allowed to affix the Mark of Conformity according to Article 11 in the Council Directive 96/98/EC on Marine Equipment and shall issue a Declaration of Conformity, only when the module D or E or F of Annex B in the same directive is fully complied with.

Module D: The quality system for production and testing shall be approved by the Notified Body.

Module E: The quality system for inspection and testing shall be approved by the Notified Body.

Module F: Compliance of the products to type as described in this EC Type-Examination Certificate must be verified by the Notified Body who also shall issue a of Certificate Conformity.

## USCG Approval

An U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of certificates of conformity for marine equipment" signed 17 October 2005.

